

SPL250-24R

친환경, 방수, 전기 안전규격



모델	SPL250-24R
Output Rated Voltage	24Vdc±3%
Output Rated Current	9.38A
Efficiency	min 92%
Over Voltage Limit	max 25V
Ripple & Noise max	240mVp-p
Input Rated Power	250W ±5% (전력 Limit에의한 전력 제어)
Input Rated Voltage	187 ~ 264 Vac (50~60Hz) at 85% rated power
Input Rated Current	1.9A (220Vac 60Hz)
Inrush Current	60A 이하(Cold Start)
Turn On Time	500ms (max)
Power Factor	0.55이상 (Input 220Vac 60Hz)
Protection	입력 과전압, 고온(케이스 80°C), 과전력, 단락 보호기능
Leakage Current	1mA이하 (입력220Vac 60Hz)
Operating Temperature	-30°C~50°C
Storage Temperature	-30°C~80°C
Working Humidity	완전 방수 (IP68)
Safety Standards	KC, IP68
Withstand Voltage	입력-출력간 3KVac만족
KC Certificate	HH11228-17010A
AC Input Wire	KS, ICE 60227-5, 300/500V, 0.75sq x 3C 250mm
DC Output Wire	KETI HH01046-5005, CVCTF, 300/500V, 1.5sq x 2C, 250mm
MTBF	45,000시간이상 (정격 90%이내)
Dimension(LxWxH)	210 x 68 x 38.8mm
Weight	0.84kg
Size	