

SPL200-24R

친환경, 방수, 전기 안전규격



| | |
|-----------------------|---|
| 모델 | SPL200-24R |
| Output Rated Voltage | 24Vdc±3% |
| Output Rated Current | 7.5A |
| Efficiency | min 93% |
| Over Voltage Limit | max 25V |
| Ripple & Noise max | 240mVp-p |
| Input Rated Power | 200W ±5% (전력 Limit에의한 전력 제어) |
| Input Rated Voltage | 187 ~ 264 Vac (50~60Hz) at 85% rated power |
| Input Rated Current | 1.6A (220Vac 60Hz) |
| Inrush Current | 60A 이하(Cold Start) |
| Turn On Time | 500ms (max) |
| Power Factor | 0.55이상 (Input 220Vac 60Hz) |
| Protection | 입력 과전압, 고온(케이스 80°C), 과전력, 단락 보호기능 |
| Leakage Current | 1mA이하 (입력220Vac 60Hz) |
| Operating Temperature | -30°C~50°C |
| Storage Temperature | -30°C~80°C |
| Working Humidity | 완전 방수 (IP68) |
| Safety Standards | KC, IP68 |
| Withstand Voltage | 입력-출력간 3KVac만족 |
| KC Certificate | HH11228-17009A |
| AC Input Wire | KS, ICE 60227-5, 300/500V, 0.75sq x 3C 250mm |
| DC Output Wire | KETI HH01046-5005, CVCTF, 300/500V, 1.5sq x 2C, 250mm |
| MTBF | 45,000시간이상 (정격 90%이내) |
| Dimension(LxWxH) | 183 x 68 x 38.8mm |
| Weight | 0.67kg |
| Size | |